



FLAT DETAILS RECORD OVER
 SLOPED FLOOR DECKING
 FOR ROOF DRAIN LOCATION
 SEE ROOF PLAN

SEE SK. PLAN FOR
 ROOF CONDITION

10'-0"
 3'-4" 9'-4" 3'-4"
 3'-4" 2'-2" 2'-2" 2'-2" 2'-2" 3'-4"
 4' 4'

STANDARD SEAM COPPER ROOF
 5/16" GALVAN. TYPE F
 2-0 CONTINUOUS
 1/2" INSULATION & SCOTT
 BATT VENT
 FIN CEILING-111-54
 7'-0"
 FIN CEILING-101-4"
 3'-0"
 FIN C.A. & POOL DECK - 104-4"

2-4 D&P CEILING
 ALUMINUM MYLAR VR
 R-20 WALL INSULATION

DOUBLE 2-0 WALL
 FRAMING

PROVIDE TEMP.
 SUPPORT UNDER
 THIS WALL UNTIL
 INSULATION OF
 FINISH COLUMN &
 BEAM.

INTERIOR RADIUS = 4'-0"

EXTERIOR RADIUS = 11'-4"

2-4x8 CONT. HORIZ. FRAMING
 DIMENSION @ COLUMN LOCATIONS
 BOTH SIDES
 FOR COLUMN CONSTRUCTION
 SEE:

R-20 WALL INSULATION
 ALUMINUM MYLAR VAPOR BARRIER

HEIGHT OF WINDOW VARIES

2-4x8x8 EACH SIDE CONT.
 FINISH PLATE (NIC)

VARIES
 FINISH PLATE

FINISH SILL - 101-10"

100'-10"
 T.O.W. - FRAMING

FACE OF FRAMING
 FACE OF FOUNDATION

99'-0" (VARIABLE)
 T.O.W. - BRUSH 2-0"

3/4 COX TEMP DECKING
 2-0 1/2" TEMP JOIST

3'-0"
 FIN FLOOR @ POOL DECK - 71-0"

2'-0"